



Model DC80
MFG PN:

ELECTRICAL DATA		
Rated Motor Output Power	1.5	HP
	-	kW
Rated Motor Speed	1750	r/min 60Hz
	-	r/min 50Hz
Rated Motor Voltage (+/-10%)	180	V/60Hz
	-	V/50Hz
Rated Motor Current	7.20	A (I _n) @ 60Hz
	-	A (I _n) @ 50Hz
Phase	-	∅
Locked Rotor Current @ High Voltage	-	A (I _n) @ 60Hz
FI Current @ 208V	-	A (I _n) @ 60Hz
Service Factor	1.15	@ 60Hz
	-	@ 50Hz
KVA Code	-	60Hz
	-	50Hz
Nominal Efficiency	-	% @ 60Hz
Nominal Power Factor	-	cosΦ @ 60Hz
Leads (Qty, Size)	2	-
Connection	-	-
Coil Resistance	-	Ω
Start Capacitor	-	μF/V
Run Capacitor	-	μF/V
VFD DUTY (S.F. 1.0)	RATIO	Hz
Variable Torque	-	-
Constant Torque	-	-
FULL LOAD TEMPERATURE RISE		
Full Load Temperature Rise	-	°C @ 60Hz
	-	°C @ 50Hz

GENERAL DATA		
Frame Size	145TC	
Enclosure	TEFC	
Mounting	Rigid/C-Flange	
Approximate Weight (lbs.)	45 lbs.	
Casing Material / Fan Cover	Rolled Steel	Steel
Shaft Material	1045	
NEMA Design	-	
Degree of Protection (IP)	44	
Insulation Class / Temp Rise (60Hz)	F	-
Tropicalization	NO	
Duty	Cont. / S1	
Conduit Box Location	-	
Feet Removable / Double Drilled	YES	-
Paintwork	-	
	-	
MECHANICAL DATA		
Bearing DE Side	-	
Bearing ODE Side	-	
Grease Type	-	
Compensation Ring (wavy washer)	-	
Moment of Inertia (lb-ft ²)	-	
Sound Pressure @ 3 FT dBA	-	
SITE CONDITIONS		
Ambient Temperature (°C)	40	
Meters Above Sea Level (MASL)	1000	
HAZARDOUS LOCATIONS		
CSA Certified	-	
Temperature Code	-	-

Questions? Call 1.888.286.1820